

<p><b>GK-17</b></p> <ul style="list-style-type: none"> <li>• Electrical Insulator</li> <li>• 2200 Volts/Mil</li> <li>• Water Absorption: &lt; .06%</li> <li>• Temp: 115 C</li> </ul>	<p><b>FOIL TAPE</b></p> <ul style="list-style-type: none"> <li>• Available With or W/Out PSA</li> <li>• Temp: 600 F</li> </ul>	<p><b>NEOPRENE</b></p> <ul style="list-style-type: none"> <li>• EPDM</li> <li>• Temp: -90 to 275 F</li> <li>• FM VSS No. 302</li> <li>• Excellent UV &amp; Ozone Weather Resistance</li> </ul>	<p><b>SUPERWOOL</b></p> <ul style="list-style-type: none"> <li>• Ceramic Fiber Blanket</li> <li>• Temp: 2200 F</li> <li>• UL 94 VO</li> </ul>	<p><b>NEEDED BLANKET</b></p> <ul style="list-style-type: none"> <li>• Apply Mat 409</li> <li>• Excellent Thermal Properties</li> <li>• Temp: 1000 F</li> <li>• High Tensile</li> <li>• Good Sound Absorption</li> </ul>	<p><b>THERMAVOLT</b></p> <ul style="list-style-type: none"> <li>• 430-1600 Volts/Mil</li> <li>• Temp: 220 C</li> <li>• Insulating paper bonded to both sides of PET film</li> <li>• 3M™</li> <li>• UL Recognized</li> </ul>
<p><b>FISHPAPER</b></p> <ul style="list-style-type: none"> <li>• VHR-115</li> <li>• Electrical Insulator</li> <li>• UL 94 B</li> <li>• 250 Volts/Mil</li> <li>• Water Absorption &gt; 50%</li> <li>• Temp: 220 C</li> </ul>	<p><b>PORON</b></p> <ul style="list-style-type: none"> <li>• 4701-40</li> <li>• Poly-Urethane Foam</li> <li>• UL 50</li> <li>• UL 508</li> <li>• UL 94 HBF</li> </ul>	<p><b>PVC FOAM TAPE</b></p> <ul style="list-style-type: none"> <li>• V316</li> <li>• Temp: -15 to 160 F</li> <li>• UL 94 HBF</li> <li>• FM VSS No. 302</li> </ul>	<p><b>4965</b></p> <ul style="list-style-type: none"> <li>• Double Sided Bonding Tape</li> <li>• Resistant to Plasticizers</li> <li>• Excellent for ABS Plastic Parts, Rubber, &amp; EPDM Profiles</li> </ul>	<p><b>THERMALBOND</b></p> <ul style="list-style-type: none"> <li>• V2845</li> <li>• Urethane Bonding Tape</li> <li>• Excellent Shear Strength</li> <li>• Temp: -40 to 200F</li> </ul>	<p><b>TC-2006</b></p> <ul style="list-style-type: none"> <li>• Thermally Conductive Gap Filler</li> <li>• Scrim Reinforced</li> <li>• UL 94 VO</li> </ul>
<p><b>VHB</b></p> <ul style="list-style-type: none"> <li>• 3M™-4950</li> <li>• UL 746 C</li> <li>• Replaces Rivets, Spot Welds, Liquid Adhesive, &amp; Other Fasteners</li> </ul>	<p><b>FR-700</b></p> <ul style="list-style-type: none"> <li>• Electrical Insulator</li> <li>• Temp: 115 C</li> <li>• UL 94 VO</li> <li>• 1500 Volts/Mil</li> </ul>	<p><b>SOLID RUBBER</b></p> <ul style="list-style-type: none"> <li>• Measured in Durometer</li> <li>• Temp: 240 F</li> <li>• Tensile: 1500psi</li> <li>• MV SS 302</li> </ul>	<p><b>DIFFUSER FILM</b></p> <ul style="list-style-type: none"> <li>• Available in White &amp; Clear</li> <li>• Used for Different Lighting &amp; Electronic Applications</li> <li>• Test Method: ASTM D1476, D523, D1033, D882, D257, D149</li> </ul>	<p><b>TAI3047</b></p> <ul style="list-style-type: none"> <li>• 3M™</li> <li>• Acoustical Insulator</li> <li>• Sound Absorbing Properties</li> <li>• Temp: 120 C for 2000 hours</li> <li>• FMVSS 302</li> <li>• Will Not Absorb Water</li> </ul>	<p><b>CEQUIN</b></p> <ul style="list-style-type: none"> <li>• Inorganic Paper</li> <li>• Temp: 220 C</li> <li>• 3M™</li> </ul>
<p><b>HT-800</b></p> <ul style="list-style-type: none"> <li>• Silicone Foam</li> <li>• With or W/Out PSA</li> <li>• Temp: 392 F</li> <li>• UL 94 VO</li> </ul>	<p><b>MANNGLASS</b></p> <ul style="list-style-type: none"> <li>• Temp: &gt;1800 F</li> <li>• Glass Fiber Paper</li> <li>• Available in Black &amp; White</li> </ul>	<p><b>CROSS-LINK</b></p> <ul style="list-style-type: none"> <li>• Temp: 160 F</li> <li>• Single or Double Coated</li> </ul>	<p><b>MELAMINE</b></p> <ul style="list-style-type: none"> <li>• Temp: 392 F</li> <li>• UL 94 VO</li> <li>• Acoustical &amp; Thermal Insulation</li> </ul>	<p><b>ETHER</b></p> <ul style="list-style-type: none"> <li>• Temp: 228 F</li> <li>• UL 94 HF 1</li> </ul>	<p><b>R10400</b></p> <ul style="list-style-type: none"> <li>• Silicone Foam</li> <li>• Temp: 500 F</li> <li>• UL 94 VO</li> </ul>

